

短型气囊



短型气囊本身气囊长度较短，适用于允许使用长度较短的管道内。气囊由高质量天然橡胶及丁苯橡胶混合制成，并由织物覆盖。有固定尺寸和可变尺寸气囊可供选择。适用温度为 $-40\sim 70^{\circ}\text{C}$ 。适用管径范围为 $30\sim 1000\text{mm}$ 。

该系列常规型号气囊不防酸、碱、高温及化学腐蚀。可根据客户使用环境需求定制NBR丁腈橡胶（耐油）、CR氯丁橡胶（耐燃、耐酸碱）或EPDM乙丙橡胶（耐酸碱、耐热寒）。

零件号	名义尺寸	最小管径 (mm)	最大管径 (mm)	最大工作压力 (bar)	产品直径 (mm)	橡胶部分长度 (mm)	重量 (kg)
ABE20	0.8"	20	21	2.5	19	25	0.10
ABE25	1"	24	25	2.5	23	25	0.10
ABE30	1-1/4"	30	32	2.5	29	30	0.15
ABE40	1-1/2"	38	42	2.5	37	40	0.15
ABE50	2"	48	54	2.5	45	75	0.25
ABE60	2-1/2"	59	65	2.5	58	90	0.35
ABE75	3"	72	78	2.5	69	110	0.45
ABE100	4"	90	105	2.5	88	150	0.6
ABE150	6"	150	150	2.5	90	150	1.1
ABE200	8"	200	200	2.5	138	200	1.6
ABE250	10"	250	250	2.5	180	250	2.2
ABE300	12"	300	300	2.5	225	300	3.5
ABE400	16"	400	400	2.5	380	450	4.4
ABE500	20"	500	500	2.5	485	450	5.5
ABE600	24"	600	600	2.5	585	450	6.3
ABE800	32"	800	800	2.5	780	1200	25.0

ABE2030	0,78"-1,2"	20	30	2,5	18	100	0,12
ABE3040	1 1/4"-1 1/2"	30	49	2.5	29	100	0.16
ABE3050	1 1/4"-2"	30	50	2.5	29	100	0.18
ABE4050	1,6 "-2"	40	50	2.5	38	80	0.18
ABE5075	2"-3"	50	75	2.5	45	100	0.30
ABE70100	3"-4"	70	100	2.5	65	100	0.40
ABE100150	4"-6"	90	155	2.5	88	150	0.75
ABE150200	6"-8"	150	200	2.5	138	200	1.1
ABE200250	8"-10"	200	250	2.5	180	250	1.6
ABE250300	10"-12"	250	300	2.5	225	300	2.2
ABE300350	12"-14"	300	350	2.5	280	300	3.5
ABE400450	16"-18"	400	450	2.5	380	450	4.2
ABE500550	20"-22"	500	550	2.5	480	550	4.4
ABE600650	24"-26"	600	650	2.5	580	650	6.5
ABE8001000	32"-40"	800	1000	2.5	780	1200	26.0

短型气囊背压表

管道直径 (mm)	50	75	100	150	200	250	300	350	400	450	500	550	600	650
气囊型号 (mm)														
50-75	1.8	1.5												
70-100		1.7	1.5											
100-150			1.8	1.5										
150-200				1.8	1.5									
200-250					1.8	1.5								
250-300						1.5								
300-350							1.8	1.5						
400-450									1.8	1.5				
500-550											1.8	1.5		
600-650													1.8	1.5