

固定尺寸高压机械式测试气囊



型号1



型号2

该系列气囊用于封堵管道、维修、水压检测及在管道内焊接点的密封性测试，适用温度可达100°C。该气囊易于安装，可用于支管道中。选用耐油的丁腈橡胶垫，坚固耐用。也可定制更高的背压和其他尺寸。

零件号 (型号1)	重量 (kg)	零件号 (型号2)	重量 (kg)	名义尺寸 (mm)	最小管径 (mm)	最大管径 (mm)	最大背压 (bar)	导流直径 (inch)
AMSSH-PPTP2001	3.8	AMSSH-PPTP2002	5.7	200	193	206	6	1/2"
AMSSH-PPTP2501	4.5	AMSSH-PPTP2502	6.8	250	244	257	6	1/2"
AMSSH-PPTP3001	6.8	AMSSH-PPTP3002	10.2	300	290	310	6	1/2"
AMSSH-PPTP3501	8.0	AMSSH-PPTP3502	12.0	350	340	360	6	1/2"
AMSSH-PPTP4001	10.0	AMSSH-PPTP4002	15.0	400	396	412	6	1/2"
AMSSH-PPTP4501	12.0	AMSSH-PPTP4502	18.0	450	445	460	6	1/2"
AMSSH-PPTP5001	14.0	AMSSH-PPTP5002	21.0	500	490	508	6	1/2"
AMSSH-PPTP5501	16.0	AMSSH-PPTP5502	24.0	550	540	560	6	1/2"
AMSSH-PPTP6001	19.0	AMSSH-PPTP6002	29.0	600	590	610	6	1/2"
AMSSH-PPTP6501	20.7	AMSSH-PPTP6502	31.0	650	640	660	6	1/2"
AMSSH-PPTP7001	22.3	AMSSH-PPTP7001	34	700	690	710	6	1/2"
AMSSH-PPTP7501	25.0	AMSSH-PPTP7502	38.0	750	740	760	6	1/2"
AMSSH-PPTP8001	27.0	AMSSH-PPTP8002	41.0	800	790	810	6	1/2"
AMSSH-PPTP8501	27.0	AMSSH-PPTP8502	41.0	850	840	860	6	1/2"
AMSSH-PPTP9001	29.0	AMSSH-PPTP9002	44.0	900	890	910	6	1/2"
AMSSH-PPTP9501	31.0	AMSSH-PPTP9502	47.0	950	940	960	6	1/2"
AMSSH-PPTP10001	33.0	AMSSH-PPTP10002	50.0	1000	990	1010	6	1/2"