

多尺寸弹性检测气囊 1.5 bar



此款气囊中间带导流管，适用于管道使用过程中带水作业的情况，同时导流管有消防水带接头，便于与消防水带相接，将管内水引流至其他地方。该气囊主要用于闭水闭气测试。抗老化，适用温度范围是-40~70°C，直径范围是50~4200mm。该系列气囊可根据不同使用需求选择单导流（零件号尾数01）或双导流型（零件号尾数02）。

零件号	名义尺寸 (mm)	最小管径 (mm)	最大管径 (mm)	最大工作压力 (bar)	产品直径 (mm)	长度 (mm)	导流直径 (inch)	产品重量 (kg)
APB501001	50-100	50	100	1.5	45	330	1/4"	1.0
APB501002	50-100	50	100	1.5	45	330	2x1/16"	1.2
APB701501	70-150	70	150	1.5	64	400	1/2"	1.2
APB701502	70-150	70	150	1.5	64	400	2x1/4"	1.3
APB1002001	100-200	100	200	1.5	88	500	1"	1.8
APB1002002	100-200	100	200	1.5	88	500	1/4"+1/2"	1.9
APB1503001	150-300	150	300	1.5	138	580	2"	4.0
APB1503002	150-300	150	300	1.5	138	580	2x1"	4.2
APB2004001	200-400	200	400	1.5	185	680	2"	7.2
APB2004002	200-400	200	400	1.5	185	680	2x1"	7.4
APB2005001	200-500	200	500	1.5	185	820	2"	8.0
APB20050002	200-500	200	500	1.5	185	820	2x1"	9.0
APB3006001	300-600	300	600	1.5	285	850	2"	11.0
APB3006002	300-600	300	600	1.5	285	850	2"+1"	11.7
APB3757501	375-750	375	750	1.5	360	1000	2"	18.0
APB3757502	375-750	375	750	1.5	360	1000	2"+1"	20.0
APB50010001	500-1000	500	1000	1.5	485	1200	2"	27.0
APB50010002	500-1000	500	1000	1.5	485	1200	2x2"	28.0
APB60012001	600-1200	600	1200	1.5	585	1400	2"	35.0
APB60012002	600-1200	600	1200	1.0	585	1400	2x2"	36.0
APB60016001	600-1600	600	1600	1.0	590	1900	2"	47.0
APB80012001	800-1200	800	1200	1.5	780	1200	2"	35.0
APB80012002	800-1200	800	1200	1.5	780	1200	2x2"	38.0
APB80016001	800-1600	800	1600	1.5	780	1600	2"	45.0
APB80016002	800-1600	800	1600	1.5	780	1600	2x2"	48.0
APB80022001	800-2200	800	2200	1.5	790	3200	2"	90.0
APB80022002	800-2200	800	2200	1.5	790	3200	2x2"	100.0
APB140028001	1400-2800	1400	2800	1.5	1300	3600	4"	250.0
APB140036001	1400-3600	1400	3600	1.5	1300	4000	4"	325.0
APB140042001	1400-4200	1400	4200	1.5	1300	6000	4"	580.0
APB160036001	1600-3600	1600	3600	1.0	1580	3600	2"	250.0